

Data sheet

MODEL	CTS-MC6560
ELECTRICAL SPECIFICATIONS	
Energy	65KWH
Output power	60KW
Output voltage	DC200V-750V
Output current	0-150A
Input power	30KW
Communication	OCPP1.6J
Safety standard	IEC62619, UN38.3, MSDS.CE
Adaptive vehicle model	Van, Passenger cars, commercial vehicles, and special vehicles
MECHANICAL SPECIFICATIONS	
Dimensions (L x W x H)	1576*925*1050mm
IP level	IP54
Weight	<840KG
CHANG GUN & DISPLAY SPECIFICATIONS	
Charging gun cable	7M
Display	7 inches
Charging gun standard	CCS1/CCS2/CHAdeMO/GBT
CHARGE SPECIFICATIONS	
Input Protocol	CCS (60KW) & 380VAC(20KW)
Reserved AC Output interface	20KW(customized function)
TEMPERATURE SPECIFICATIONS	
Charge Temperature Range	0~45℃
Discharge Temperature Range	-20~60℃
Recommended Operating Temp	15~35℃
Storage Temperature & Humidity Range(Less than 3 months)	-10~35℃, 45~75%RH
Recommended Storage Temp	15~35℃, 45~75%RH
WARRANTY	
Warrenty	2 yesrs